



Epoxy Flooring

ANTI-SKID

Anti-Skid Selection Recommendations

In general epoxies can become very slippery when wet or greasy if inadequate texture is present. Tera-Lite, Inc. is very concerned with the safety of our customers and we recommend specific textures for different areas and their usage.

SMOOTH

Dry areas or areas that will not have foot traffic of any kind, such as trenches, and per the Health Department, underneath equipment and counters in kitchen applications for ease of cleaning.

Note: There is no such thing as a perfectly smooth glass finish; there will always be some debris from the atmosphere (dust, lint, etc.) that will cause imperfections in the surface.

STIPPLE (AKA ORANGE PEEL)

Dry areas only where smooth is not desirable. This offers little to no anti-skid. This is the only texture for walls and ceilings.

#100 MESH (ADDITIONAL COST TO INSTALL THIS TEXTURE)

The selection of this texture will require an additional seal coat be applied and therefore an additional cost will apply.
Dry areas only where smooth is not desirable. This offers little to no anti-skid.

Note: This silica sand is so fine it is like a powder and requires an additional thin seal coat so that it does not sink into the epoxy.

#70 MESH

Areas such as dry storage, restrooms with toilets and sinks only, and inside walkways, etc.

ALUMINUM OXIDE #60

Similar to #70 Mesh, Aluminum Oxide #60 is a higher quality aggregate with sharper edges and is longer lasting. Areas such as dry storage, restrooms with toilets and sinks only, and inside walkways, etc.

FLINTSHOT

ALL wet areas, kitchens, shower rooms, wash down areas, and outside walkways that are not high traffic .

ALUMINUM OXIDE #36

Similar to Flintshot, Aluminum Oxide #36 is a higher quality aggregate with sharper edges and is longer lasting. ALL wet areas, kitchens, shower rooms, wash down areas, and outside walkways that are not high traffic.

ROLL-SEED-ROLL / SSF

High traffic areas, areas with extreme exposure to liquids, outdoor locations

This letter represents Tera-Lite's recommendations only from our experience, but the final decision must be made by the owner or the owner's representative. If an anti-skid selection is decided upon that Tera-Lite considers being a safety concern, a release shall be signed.